# **FILIATRINOS DAM**

CONSTRUCTION



# **Construction Company**




- Founded in 1987
- Ranks among the top construction groups in Greece
- International presence in 7 countries
- Basic activities:
  - Renewable energy sources projects
  - Telecommunications
  - Environmental projects
  - Construction projects
  - Infrastructure projects

#### Area of construction

- Near Filiatra city (about 10.000 people)
- Agriculture is the mainstay of region economy





# Features of the dam (1/2)

- Project budget 35.000.000 €
- Material of embankment: 430.000 m<sup>3</sup> of lean roller compacted concrete (51kg cement and 23kg flying ash)
- Length: 246 m
- Width: 7m + 2m both sidewalks uppon the coronation and 96m upon the foundation
- Length of spillway 24 meters
- Crest level +215,20m and 212,00m on the spillway
- Height: 55m from foundation and 45m from natural ground


# Features of the dam (2/2)

Waterproofing by reinforced concrete slab of 10.200m<sup>2</sup>

Upstream slope

0.8

- Reservoir volume: 7.810.000 m³
- Purpose of the dam: irrigation of 30.000.000 m²
- Usable volume of reservoir: 7.630.000 m³
- Annual water volume available for consumption: 9.000.000 m<sup>3</sup>
- Untill 22/10/2012 the embankment of the dam has been made up to the level +193,90 m





The site of the dam before the construction



Exploratory tunnel during the project design



The site of the dam during the construction



Trimming and transplanting olive trees



Temporary river diversion



Shortly after the start of excavation



Excavations in grades for the transition of the machinery and equipment:

1) ground core sampling 2) grout curtain / umbrella



Excavations in grades for the transition of the machinery and equipment:

1) ground core sampling 2) grout curtain / umbrella



Ground core sampling



Excavation for the construction of the plinth



Cement grouting



Drilling for the plinth anchors




Plinth anchors



#### Anchors



Building the plinth



Plinth's head (waterproofing by PVC and copper)



The plinth



The plinth on the right side finished



The plinth on the left side during the construction



The plinth on the left side



General excavation



Facilities for the lean RCC and concrete production



Installation of belt conveyors



Installation of belt conveyors



Belt conveyors



Trial test section (by lean RCC)



Compaction test on the trial section



Ready to begin the embankment of the dam



Constructing a part of the embankment for the final diversion of the river



Constructing a part of the embankment for the final diversion of the river



Box culvert for the final diversion of the river



Box culvert for the final diversion of the river



Box culvert for the final diversion of the river



The final diversion finished. Excavations on the back



Preparation for the embankment on the left side



Building the final section of the plinth



Embankment on the left side



Anchors on the bottom of the spillway



Grouting the anchors



Tranquil basin



Foundation of the tranquil basin



Building the bridge over the tranquil basin



The main upper drainage pipe



Building the drainage culvert



Building the drainage culvert



The drainage culvert finished



The drainage culvert finished



Upstream slope











DEC 2011 | JAN 12 | JU

JUN 12

**SEP 12** 

**TODAY** 



Upstream side



Downstream side



Downstream steps and the spillway

# Thank you for your attention

